

EXpert² IP Controller

Networkable Access Control Unit

A fully featured, networkable access control unit - the EXpert² boasts a high specification with supervised inputs and relays, making it suitable for monitoring and signalling alarm conditions as well as integration with intruder alarms and Building Management Systems.

The expansion capabilities of this controller make it highly versatile and enables the access control system to be easily added to at a later date. The EXpert² is the ideal platform for those who demand the most from an access control system.

Key Features

- 47000 card capacity
- 2 reader, 1 or 2 door controller
- Main reader output formats supported
- 4A mains power supply unit
- Standby battery facility
- Fully expandable - up to 7 EXpert² slave units per master giving control of up to 16 doors
- Optional 32 input, 16 output module
- Local programming using EXkeypad accessory
- 1,000 event buffer
- Compatible with EXgarde PC software
- Robust enclosure design
- Integrated tamper switch
- Supports supervised inputs
- High capacity Form C change-over relays
- Integral TCP/IP port
- 3-year warranty



Ordering Information

Description: EXpert² IP advanced 2 door access control unit with TCP/IP port.

Part No. 5002-3012

Description: EXpert² slave control unit.

Part No. 5002-3042

Description: EXkeypad Programmer.

Part No. 5002-2070

Description: 32 input 16 output card for EXpert.

Part No. 5002-3060


Description: EXPander² 2 door expansion module for EXpert.

Part No. 5002-3063

Specification

TDSi Part No.	5002-3012
Dimensions	390 x 410 x 90 mm
Weight	5.7kg
Operating Environment	-5°C to + 45°C, 0 to 95% RH (non-condensing)
Power	
Input	100 - 240Vac, 50 - 60Hz, 1.8A Max
Output	13.8Vdc (Nominal) (4A Max)
Battery	10.5 to 12.3Vdc, 1 x 7Ah Sealed lead acid (optional)
Features	
Max Cards	47000
Doors	1 or 2
Readers	Maximum of 2 using the majority of reader, keypad and biometric technologies including those with standard clock & data, 26-bit Wiegand and HID standard 37-bit (H10302) output formats.
Inputs	8 in total; 6 spare when used in 1 door mode or 4 spare when used in 2 door mode for monitoring other equipment. Can be increased with the use of EXpert ² and EXin / EXout module.
Outputs	4 changeover relay outputs (30V, 2A contact rating) in total; 3 spare when used in 1 door mode or 2 spare when used in 2 door mode for controlling other equipment. Can be increased with the use of EXpert ² and EXin/EXout module.
Time Groups	64
Anti-Passback	Timed and true
Mantrap Function	Yes
Communications	RS232, RS485, Ethernet (TCP/IP) with in-built RS-485 converter for up to 30 downstream controllers (EXpert2 IP model only)

Typical installation



DS0007 - Issue 11